
Please contact the factory for parts and repairs. Always include complete description, part no. and nameplate data. IDEAL INDUSTRIES, INC.
Sycamore, Illinois
IDI ELECTRIC (Canada) LTD.
Ajax, Ontario

REPAIR PARTS LIST

Product No.

45-170 thru 45-188



Item	No. Req'd.	Part Description	Part No
1	1	Left Hand Frame	K-2243
	1	Right Hand Frame	K-2277
3	2	Handles	K-1853
2 3 4	4	Blade and Gripper Screws	355.2
5	1	Stationary Gripper 45-170, 173, 176, 180, 183 and 186 Stationary Gripper 45-171, 172, 174, 175, 177, 178,	L-5215
		179, 181, 182, 184, 185, 187, 188	L-5217
6	1	Movable Gripper	L-5212
7	1 pr	Blades (listed on reverse side)	1
8	1	Blade Retaining Plate	L-4536
9	2	Links	L-4377
10	2	Link Pins	281.51
11	1	Latch	L-4384
12	1	Latch Spring	L-4388
13	2	Latch Stud	L-5094
14	1	Pivot Spring Cover	L-5093
15	1	Pivot Spring	L-5092
16	1	Pivot Shaft Screw	356.2
17	1	Pivot Shaft Lockwasher	633.17
18	1	Pivot Shaft	L-5095
19	1	Handle Spring In addition to the above the following parts are included on strippers 45-180 thru 188	L-4387 L-5269
20	+ 1	Short-Stop Latch Assembly which includes:	K-2272
21	1	Short-Stop Latch Short-Stop Latch Pivot Stud	L-5272
22	1		L-5271
23	1	Short-Stop Latch Spring Short-Stop Latch Stud	L-5271
23	1	Transparent Faced Wire Gage Assembly which includes:	L-32/3
25	1	Wire Gage Face Plate	L-5800
26	1	Wire Gage Face Flate Wire Gage Stud	L-5152
26	1 1	Wire Gage Stud Adjusting Screw	353.61
<i>2,1</i>	_	Adjusting Sciew	333.01

	Part Description	Part No.
	Custom Stripmaster Frames Only	i filian ikani w
45-170, -1	73, -176 (less blades)	L-5616
45-171, -1	72, -174, -175, -177, -178, -179 (less blades)	L-5617
45-180, -1	83, -186 (less blades)	L-5618
45-181, -1	82, -184, -185, -187, -188 (less blades)	L-5619
	IMPORTANT NOTICE	
	e is manufactured to meet Military Specification in the following two types:	
	Type E - Rated for 600 volts Type EE - Rated for 1000 volts	
size for s	olt wire is approximately .010 larger in diameter ize than the 600 volt, due to the additional inecessary to obtain the higher voltage rating.	
	your wire specifications when ordering Teflon f in doubt, send samples to us for positive tions.	
	Available Blades for "Custom Teflon" Stripmaster:	
	For Type E (600 volts)	
	10-14 Ga. 3 holes for 45-176 and -186	L-5559
	16-26 Ga. 6 holes for 45-177 and -187	L-5560
	26-30 Ga. 3 holes for 45-178 and -188	L-5561
	For Type EE (1000 volts)	
	10-14 Ga. 3 holes for 45-173 and -183	L-5562
	16-26 Ga. 6 holes for 45-174 and -184	L-5563
	26-30 Ga. 3 holes for 45-175 and -185	L-5564
	wires which do not necessarily meet the above pecifications and other similar hard-to-strip	
	10.1/ 0- 2.1-1 5 /5.170 1.100	T 5010
	10-14 Ga. 3 holes for 45-170 and -180	L-5210
	16-26 Ga. 6 holes for 45-171 and -181 26-30 Ga. 3 holes for 45-172 and -182	L-5211 L-5436
For "Milen	e" insulated 30 Ga. solid conductor wire:	
	30 Ga. 3 holes	L-7625